

## ■ General Description

The DH479 Omnipolar Hall effect sensor IC is fabricated from mixed signal CMOS technology. It is comprised of two Hall plates and a CMOS output driver, mainly designed for battery-operation. The total power consumption in normal operation is typically  $9\mu\text{W}$  with a 3V power source. either north or south poles of sufficient strength will turn the output on. The output will be turned off under no magnetic field. While the magnetic flux density ( $B$ ) is larger than operating point (BOP), the output will be turned on (low), the output is held until  $B$  is lower than release point (BRP), and then turned off.

The DH479 is available in many flexible packaging options, such as SOT23-3L/SIP-3L. Operating temperature range of the DH479 is from -40°C to 85°C.

## ■ Features



- 3uA Micro power design
- 2.4V to 5.5V battery operation
- CMOS Output
- Operation with North or South pole(omnipolar)
- High sensitivity and high stability of the magnetic switching points
- High resistance to mechanical stress
- Digital output signal
- Good RF noise immunity
- -40°Cto 85°Coperating temperature
- SOT23-3L/SIP-3L(TO92S) package

## ■ Applications

- Smart meter
- toys
- Cover switch in Notebook PC/PDA
- Contact-less switch in consumer products
- Solid State Switch
- Handheld Wireless Handset Awake Switch
- Lid close sensor for battery-powered devise

## ■ Pin Configuration

(Top View)



Pin Name	Pin		Description
	SOT23-3L	SIP-3L	
VCC	1	1	IC Power Supply
OUTPUT	2	3	It is low state during the S/N magnetic field
GND	3	2	IC Ground

## ■ Application Circuit




Figure 1, application circuit

Note:  $C_{IN}$  is for power stabilization and to strengthen the noise immunity, the recommended capacitance is  $0.1\sim1\mu\text{F}$ .

## ■ Ordering Information

Part Number	Package Type	Packing Qty	B <sub>OP</sub> (Gauss)	B <sub>RP</sub> (Gauss)	Temperature	Eco Plan	Lead
DH479	SOT23-3L	3000pcs/Reel	±20(Typ.)	±14(Typ.)	-40~ +85°C	ROHS	Cu
DH479	SIP-3L	1000pcs/Bag	±20(Typ.)	±14(Typ.)	-40~ +85°C	ROHS	Cu

## ■ Block Diagram




Figure 2, Block Diagram Of DH479

## ■ Absolute Maximum Ratings<sup>1</sup> ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Rating	Unit
VDD to GND	V <sub>CC</sub>	-0.3 to 6	V
Magnetic Flux Density	B	Unlimited	
Storage Temperature Range	T <sub>S</sub>	-65 to +150	°C
Operating Junction Temperature Range	T <sub>J</sub>	-40 to 150	°C
Maximum Power Dissipation	P <sub>D</sub>	230	mW
		300	
Maximum Soldering Temperature (at leads, 10 sec)	T <sub>LEAD</sub>	260	□

## ■ Recommended Operating Conditions ( $T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Rating	Unit
Supply Voltage	V <sub>DD</sub>	Operating	2.4 ~ 5.5	V
Operating Temperature Range	T <sub>A</sub>	Operating	-40 ~ +85	°C

## ■ Electrical Characteristics

(Unless otherwise noted, typical values are at  $T_A=25^\circ\text{C}$ ,  $V_{DD}=3\text{V}$ )

Symbol	Parameter	Conditions	Min	Typ.	Max.	Unit
$V_{OL}$	Output On Voltage (Low side)	$I_{OUT}=-1\text{mA}$	-0.3	0.1	0.3	V
$I_{OFF}$	Output Leakage Current	$V_{OUT}=5.5\text{V}$ , Output off	-	<0.1	1	$\mu\text{A}$
$I_{DD(EN)}$	Supply Current	Chip enable, $T_A=25^\circ\text{C}$ , $V_{DD}=3\text{V}$	-	2.1	2.4	mA
$I_{DD(EN)}$		Chip enable, $T_A=-40\sim85^\circ\text{C}$ , $V_{DD}=2.4\sim5.5\text{V}$	-	2.1	3	mA
$I_{DD(DIS)}$		Chip disable, $T_A=25^\circ\text{C}$ , $V_{DD}=3\text{V}$	-	0.9	1.7	$\mu\text{A}$
$I_{DD(DIS)}$		Chip disable, $T_A=-40\sim85^\circ\text{C}$ , $V_{DD}=2.4\sim5.5\text{V}$	-	0.9	2	$\mu\text{A}$
$I_{DD(AVG)}$		Average supply current, $T_A=25^\circ\text{C}$ , $V_{DD}=3\text{V}$	-	3	5	$\mu\text{A}$
$I_{DD(AVG)}$		Average supply current, $T_A=-40\sim85^\circ\text{C}$ , $V_{DD}=2.4\sim5.5\text{V}$	-	3	6	$\mu\text{A}$
$T_{awake}$		-	5	20	35	$\mu\text{s}$
$T_{period}$	Period	-	-	40	60	ms
D.C.	Duty Cycle	-	-	0.05	-	%

## ■ Magnetic Characteristics

$V_{DD}=3\text{V}, T_a=25^\circ\text{C}$					
Parameter	Symbol	Min.	Typ.	Max.	Unit
South Pole Operate point	BOPS	9	20	28	Gauss
South Pole Release point	BRPS	5	14	25	Gauss
North Pole Operate point	BOPN	-28	-20	-9	Gauss
North Pole Release point	BRPN	-25	-14	-5	Gauss
Hysteresis	BHYS	2	6	12	Gauss

## ■ Output VS Magnetic Pole

Part Number	Magnetic Pole	Test Conditions	Output
DH479	South Pole	$B > BOPS$	Low
DH479	South Pole	$B < BRPS$	High
DH479	North Pole	$B < BOPN$	Low
DH479	North Pole	$B > BRPN$	High




Figure 3, Magnetic Operational Characteristics Of DH479

### ■ Hall Sensor Location




Figure4, Hall Sensor Location

### ■ Land Pattern (for reference only)





Figure 5, Land Pattern Dimension (SOT23-3L)

## ■ Package Information


1)SOT23-3L



Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.050	1.15	1.250	0.041	0.045	0.049
A1	0.000	0.050	0.100	0.000	0.002	0.004
A2	1.050	1.100	1.150	0.041	0.043	0.045
b	0.300	0.400	0.500	0.012	0.016	0.020
c	0.100	0.150	0.200	0.004	0.006	0.008
D	2.820	2.920	3.020	0.111	0.115	0.119
E	1.500	1.600	1.700	0.059	0.063	0.067
E1	2.650	2.800	2.950	0.104	0.110	0.116
e1	1.800	1.900	2.000	0.071	0.075	0.079
e	0.950 REF			0.037 REF		
L	0.300	0.450	0.600	0.012	0.018	0.024
theta	0°	4°	8°	0°	4°	8°

## ■ Package Information

2)SIP-3L



Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.90	3.00	3.10	0.11	0.12	0.12
b	0.35	0.39	0.56	0.01	0.02	0.02
b1		0.44			0.02	
c	0.36	0.38	0.51	0.01	0.01	0.02
D	3.9	4.0	4.2	0.15	0.16	0.16
E	1.42	1.52	1.62	0.06	0.06	0.06
E1		0.75			0.03	
e		1.27			0.05	
e1		2.54			0.10	
L	13.50	14.50	15.50	0.53	0.57	0.61
L1		1.60			0.06	
Θ1		6°			0.24°	
Θ2		3°			0.12°	
Θ3		45°			1.77°	
Θ4		3°			0.12°	